9/C COMPOSITE 32113059 CT-E991A

FIVE CONDUCTOR COMPONENT

SHIELDED:

FIVE (5) #24 19/36 TC INSULATED WITH .010" PVC

CABLED TOGETHER WITH FILLER

WRA WITH A MYLAR TAPE AND A #24 7/32 TC DRAIN WIRE

WRAP WITH ALUMINUM/MYLAR TAPE SHIELD (FOIL FACING IN)

1) BLACK 2) BROWN 3) GREEN 4) RED 5) WHITE

THREE SINGLES: THREE (3) #18 41/34 TC INSULATED WITH .010" PVC

BROWN
ORANGE
RED

ONE SINGLE: ONE (1) #18 41/34 TC INSULATED WITH .010" PVC

1) GREEN-YELLOW

CABLING: CABLE THE FIVE CONDUCTOR COMPONENT AND THE FOUR

SINGLES TOGETHER WITH FILLER

TAPE SEPARATOR: WRAP WITH A PAPER TAPE

JACKET: .060" PRESSURED 105°C BLACK PVC

<u>OD</u>: .380" MAX

PRINT IN WHITE: E83208 RU STYLE 2661 105°C 300V VW-1...LL52835 CSA AWM I/II A/B

(0741) 105°C 300V FT-4...ROHS...CE

11/7/2019