

ALPHA WIRE

Part Number: 19-2336

Issue: A

Page 1 of 1 Pages

Issue Date:

9/17/2019

Cable Specification

<u>Component 1</u>	7 COND
<u>Conductor:</u>	26 (7/34) AWG TC
<u>Insulation:</u>	0.010" Wall, Nom. SR-PVC
Color Code:	7 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED
<u>Component 2</u>	8 COND
<u>Conductor:</u>	22 (7/30) AWG TC
<u>Insulation:</u>	0.010" Wall, Nom. SR-PVC
Color Code:	1 SOLID COLORS/ 8 STRIPED/ 0 NUMBER CODED
<u>Final Assembly</u>	2 Components
<u>Shield:</u>	AM Foil Tape, 25% Overlap, Min.
Drain Wire:	26 (7/34) AWG TC
<u>Jacket:</u>	0.032" Wall, Nom., PVC
Jacket OD:	0.276"
Jacket Color:	BLACK

Approvals

UL:	AWM/STYLE 1061 AWM/STYLE 2464
CSA:	NONE
MIL:	NONE
CE Compliant:	YES
ROHS Compliant:	YES
REACH Compliant:	YES

Miscellaneous

Temperature:	80 C
Voltage:	300 V _{RMS}
Put Ups:	500 FT PUTUP (CONTINUOUS)
Requested Quantity:	1000Ft.

Application Notes

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.