


TECHNICAL DATA SHEET

Diagram

外被颜色：GRAY



Description

Cable Part Code*	TBA
Cable Type	4C0.75mm ² XLP/OBS/LSZH 300 V
Cable References Standards	BS EN 50288-7,IEC 60332-3A,IEC 60332-1-2

Conductor

Conductor Material	Bare Copper
Conductor Size	0.75 mm ²
Conductor Stranding Standard	IEC 60228-Class-5

Insulation

No. of Cores/Pair/Triad/Quad	4 Cores
Insulation Material	XLP
Nom. Insulation Diameter(mm)	1.81
Insulation Color Code	Black cores with number coding 1~4

Shielding

Shielded/Unshielded	Shielded
---------------------	----------

Outer Jacket/Sheath Material

Outer Jacket Material	LSZH
Overall Diameter(+/-0.7mm)	7.0
Outer Jacket Color	GRAY
Marking	BELDEN 6409CBB04 CONTROL CABLE 300V 4 X 0.75mm ² XLPE/OBS/LSZH BS EN 50288-7-2005 <Manufacturing Date Code>

Physical/Mechanical Properties

Temperature Rating	-30~90°C
Oil Resistance	Yes
UV Resistance	Yes
Flame Retardant	IEC 60332-3A
Smoke Density as per IEC 61034-2 (Min. Light Transmittance %)	0.60
Halogen Acid Gas as per IEC 60754-1 (%)	≤ 0.5%
pH Content as per IEC 60754-2	≥ 4.3
Conductivity as per IEC 60754-2 (μS/mm)	≤ 10
Min. Bending Radius	10 X OD
Nom. Cable Weight (Kg/km)	86

Electrical Properties

Voltage Rating (V)	300V
Max. Conductor Resistance @20°C	26
Max. Mutual Capacitance Core to Core @1KHz	150
Max. Inductance to Resistance Ratio L/R	25

*Ordering stock code will be created at the time of placing the order and the stock code will include cable part code, outer jacket color & putup length.
Belden Internal Reference Number none

© 2016 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.