


TECHNICAL DATA SHEET

Cable Diagram

外被颜色：GRAY



Description

Cable Part Code*	TBD
Cable Type	3C24AWG LSZH/LSZH

Conductor

Conductor Material	Stranded Bare Copper
Conductor Size	24AWG
Conductor Stranding Standard	7X32

Insulation

No. of Cores	3
Insulation Material	LSZH
Insulation Color Code	Black, Brown, Red

Outer Jacket/Sheath Material

Outer Jacket Material	LSZH 颜色：GRAY
Nom. Overall Diameter(±0.3mm)	4.7
Jacket printed legend	BELDEN YJxxxxx 3C24 80C 300V ROHS DDDYYANN XXXXXXXM

Physical/Mechanical Properties

Temperature Range	-15°C To +80°C
UV Resistance	Yes
Flame Retardant	IEC 60332-3B
Bending Radius	10 x OD
Nom. Cable Weight (kg/km)	27.7

Electrical Properties

Voltage Rating (V)	300
Max. Conductor Resistance @20°C(Ω/km)	88

*Ordering stock code will be created at the time of placing the order and the stock code will include cable part code, outer jacket color & putup length.

Belden internal code

SZ-CA-2193

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.