


## TECHNICAL DATA SHEET

### Cable Diagram

外被颜色 : GRAY



Description	
Cable Part Code*	TBD
Cable Type	2P24AWG LSZH/LSZH

Conductor	
Conductor Material	Stranded Bare Copper
Conductor Size	24AWG
Conductor Stranding Standard	7X32

Insulation	
No. of Cores	4
Insulation Material	LSZH
Insulation Color Code	1.Red*Black, 2.Brown*Orange

Outer Jacket/Sheath Material	
Outer Jacket Material	LSZH 颜色 : GRAY
Nom. Overall Diameter(±0.3mm)	6.4
Jacket printed legend	BELDEN YJxxxxx 2P24 80C 300V ROHS DDDYYANN XXXXXXXM

Physical/Mechanical Properties	
Temperature Range	-15°C To +80°C
UV Resistance	Yes
Flame Retardant	IEC 60332-3B
Bending Radius	10 x OD

Electrical Properties	
Voltage Rating (V)	300
Max. Conductor Resistance @20°C(Ω/km)	87.6

\*Ordering stock code will be created at the time of placing the order and the stock code will include cable part code, outer jacket color & putup length.

Belden internal code

SZ-CA-2194

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.