



NEW ENGLAND WIRE TECHNOLOGIES

130 North Main St, Lisbon, NH 03585 USA

www.newenglandwire.com

Innovate. Create. Accelerate.

N13-40T-260-2

16 CONDUCTOR CABLE

28 AWG TWISTED PAIRS (6)

28 AWG SINGLES (2)

28 AWG 19/40 TINNED COPPER, .005" FEP TO .025"

+/- .001" OD-WHITE-BLACK, GREEN-YELLOW,
BROWN-ORANGE, GRAY-VIOLET, LT BLUE-BLUE, PINK-TAN

CABLE

28 AWG SINGLES (2)

TYPE T THERMOCOUPLE (1)

26 AWG SOLID CONSTANTAN SINGLE (1)

26 AWG CONSTANTAN, .005" FEP TO .026" +/- .001" OD
RED

26 AWG BARE COPPER SINGLE (1)

26 AWG BARE COPPER, .005" FEP TO .026" +/- .001" OD
BLUE

CABLE

26 AWG CONSTANTAN SINGLE (1)

26 AWG BARE COPPER SINGLE (1)

26 AWG TWISTED PAIR (1)

26 AWG SINGLES (2)

26 AWG BARE COPPER, .005" FEP TO .026" +/- .001" OD
BLUE/WHITE-BLUE/BLACK

CABLE

26 AWG SINGLES (2)

CABLE

28 AWG TWISTED PAIRS (6)

26 AWG TWISTED PAIR (1)

TYPE T THERMOCOUPLE (1) IN THE CENTER

TAPE

.001" PAPER, 25% LAP

BRAIDED SHIELD

40 AWG TINNED COPPER, 90% MIN COVERAGE

INSULATE

.026" PVC JACKET TO .214" +/- .006" OD-BLACK

MINIMUM = 1000 FEET

FINISHED WEIGHT = (31.52#/KFT) (0.0469KG/MTR)

Labeling

TWO OUTSIDE LABELS REQUIRED - One label on the flange, and one label
on the side of the reel.

Spool Size: 18" PLYWOOD-B

RoHS Compliant 2002/95/EC & 2011/65/EU & 2015/863