



Part Number: 9463

Blue Hose®, 1 Pr #20 Str TC, PO Ins Blu,Wht, OS+TC Brd, PVC Jkt, CM

[🛒 Request Sample](#)

Product Description

Blue Hose® for Data Highway Plus, 1 Pair 20AWG (7x28) Tinned Copper, PO Insulation Blu,Wht Color Code, Overall Beldfoil®+Tinned Copper Braid(55%) Shield, Blue PVC Outer Jacket, CM

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
20	7x28	TC - Tinned Copper	0.038 in	1

Conductor Count: 2

Insulation

Material	Nominal Diameter
PE - Polyethylene	0.078 in

Color Chart

Number	Color
1	Clear & Blue

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	20	7x28H mm
Braid	2	TC - Tinned Copper		55 %			

Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.238 in

Construction and Dimensions

Stranding

Twists	Diameter
2.75 twist/ft	0.154 mm

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
9.5 Ohm/1000ft	4.1 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
19.7 pF/ft	36 pF/ft

Inductance

Nominal Inductance

0.12 µH/ft

Impedance

Nominal Characteristic Impedance

78 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.6 dB/100m
10 MHz	2.1 dB/100m
50 MHz	5 dB/100m
100 MHz	7.5 dB/100m
200 MHz	11 dB/100m
400 MHz	16 dB/100m

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.54 ns/ft	66 %

Voltage

UL Voltage Rating
300 V RMS (UL AWM Style 2464)
300 (NEC Type CM) V RMS
300 V RMS (NEC Type CL2)

Electrical Characteristics Notes: DC Resistance Unbalanced: .77 Ohms/1000 ft Max

Temperature Range

Installation Temp Range:	-40°C To +80°C
UL Temp Rating:	80°C (UL AWM Style 2464)
Storage Temp Range:	-40°C To +80°C
Operating Temp Range:	-40°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	36 lbs/1000ft
Max Recommended Pulling Tension:	48 lbs
Min Bend Radius/Minor Axis:	2.4 in

Standards

Customer Part Number Reference Spec:	Allen Bradley P/N 1770-CD
NEC/(UL) Specification:	CL2, CM
CEC/C(UL) Specification:	CM
UL AWM Style:	UL Style 2464 (300 V 80°C)
CPR Euroclass:	Eca
PMSHA Specification:	P-7K-SC-182141

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Sunlight Resistance:	Yes
------------------------------------	-----

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 UL Loading
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS (UL AWM Style 2464)

Plenum/Non-Plenum

Plenum Number:	89463
----------------	-------

Part Number

Variants

Item #	Color	UPC	Length	Footnote
9463.001000	Blue		1,000 m	
9463.001829	Blue		1,829 m	
9463.0030	Blue		30 m	
9463.00305	Blue		305 m	
9463.00U152	Blue		152 m	
9463.00U305	Blue		305 m	
9463.01152	Blue		152 m	
9463.K0305	Blue		305 m	
9463 J22100	Blue, Strong	612825253549	100 ft	
9463 J221000	Blue, Strong	612825253556	1,000 ft	C
9463 J2212000	Blue, Strong	612825253563	2,000 ft	C Y
9463 J22500	Blue, Strong	612825253570	500 ft	
9463 J226000	Blue, Strong	612825253587	6,000 ft	C Z
9463 J22U1000	Blue, Strong	612825253525	1,000 ft	
9463 J22U500	Blue, Strong	612825253532	500 ft	
9463.02305	Brown		305 m	
9463.023050	Brown		3,050 m	
9463 0011000	Brown	612825253594	1,000 ft	
9463 00110000	Brown	612825253600	10,000 ft	C Z
9463 00112000	Brown	612825253617	2,000 ft	C Y
9463 0016000	Brown	612825253624	6,000 ft	C Z
9463.031829	Orange		1,829 m	
9463.03305	Orange		305 m	
9463 0031000	Orange	612825253631	1,000 ft	C
9463 00310000	Orange	612825253648	10,000 ft	C Z
9463 00312000	Orange	612825253655	2,000 ft	C Y
9463 0036000	Orange	612825253662	6,000 ft	C Z
9463.041829	Violet		1,829 m	
9463.04305	Violet		305 m	
9463 0071000	Violet	612825253679	1,000 ft	C
9463 0076000	Violet	612825253686	6,000 ft	C Z

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.
Footnote:	Y - FINAL PUT-UP LENGTH MAY VAR -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

History

Update and Revision:	Revision Number: 0.336 Revision Date: 08-22-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.