

ALPHA WIRE

Part Number: 19-2546

Issue:

Page 1 of 1 Pages

Issue Date:

10/21/2019

Cable Specification

Component 1 2 COND
Conductor: 24 (19/36) AWG TC
Insulation: 0.010" Wall, Nom. MPPE1
Color Code: 2 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED

Final Assembly 2 Components
Core Wrap: PTFE Tape, 25% Overlap, Min.
Shield: AM Foil Tape, 25% Overlap, Min.
Drain Wire: 24 (19/36) AWG TC
Jacket: 0.032" Wall, Nom., PUZH
Jacket OD: 0.218"
Jacket Color: BLACK

Approvals

UL: AWM/STYLE 21959
SUNRES
60C OIL
CSA: c(RU) AWM I/II A/B
FT2
MIL: NONE
CE Compliant: YES
ROHS Compliant: YES
REACH Compliant: NO

Miscellaneous

Temperature: 90 C
Voltage: 600 V_{RMS}
Put Ups: 1000 FT PUTUP
Requested Quantity: 1000Ft., 2500Ft., 5000Ft.

Application Notes

Waterblock tape serves to slow and sometimes cease the flow of water through a cable. However the cable has not been tested for performance under pool water. The waterblock tape absorbing properties will absorb up to a certain point.

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.