

## ALPHA WIRE

Part Number: 19-2548

Issue:

Page 1 of 1 Pages

Issue Date:

10/22/2019

### Cable Specification

Component 1 3 PAIR  
Conductor: 24 (19/36) AWG TC  
Insulation: 0.010" Wall, Nom. MPPE1  
Color Code: ALPHA WIRE COLOR CODE A  
Pair: 2/Cond Cabled Together

Final Assembly 3 Components  
Core Wrap: PTFE Tape, 25% Overlap, Min.  
Shield: AM Foil Tape, 25% Overlap, Min.  
Drain Wire: 24 (19/36) AWG TC  
Jacket: 0.032" Wall, Nom., PUZH  
Final OD: 0.267" Nom.  
Jacket Color: BLACK

#### Approvals

UL: AWM/STYLE 21959  
60C OIL  
SUNRES  
CSA: c(RU) AWM I/II A/B  
FT2  
MIL: NONE  
CE Compliant: YES  
ROHS Compliant: YES  
REACH Compliant: NO

#### Miscellaneous

Temperature: 90 C  
Voltage: 600 V<sub>RMS</sub>  
Put Ups: 1000 FT PUTUP  
Requested Quantity: 1000Ft., 2500Ft., 5000Ft.

#### Application Notes

Waterblock tape serves to slow and sometimes cease the flow of water through a cable. However the cable has not been tested for performance under pool water. The waterblock tape absorbing properties will absorb up to a certain point.

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

#### PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.