

18/2 Type SJTOW White

SJTOW cable, rated at 300 volts, has excellent oil resistant and weather resistant characteristics. Generally used in flexible power cords, it is designed for equipment used where industrial and wet environments are present.

Design Number 10138
Part Number Table 1
Customer Number N/A

CONSTRUCTION


Conductor: Stranded bare copper
Conductor Size: 18AWG(41/34)
Insulation: Polyvinyl chloride (PVC)
Insulation Avg. Thickness: 0.030"(Nom.)
Insulation Diameter: 0.106"(Nom.)
Jacket Material: Polyvinyl chloride (PVC)
Jacket Avg. Thickness: 0.030"(Nom.)
Overall Diameter: 0.287"(Nom.)
Jacket Color: White

Print Legend:

E486041 IH (UL) SJTOW VW-1105°C 300V 2/C 18AWG(0.823 mm²) Oil Resistant
c(UL) SJTOW FT2 105°C 300V 2/C 18 AWG (0.823 mm²)

Table 1

| Part Number | Jacket Color |
|-------------|--------------|
| 32113243 | White |
| 32115741 | White |



Color Code: 1. Black 2. White

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): 105°C
Operating Voltage: 300V
Conductor Resistance @ 25°C: 22.8 Ω/km Max
Flame Test : UL VW-1 and CSA FT2

SAFETY CHARACTERISTICS

RoHS Compliance: European Directive 2015/863/EU
Approvals: UL, the basic standard is UL 62 "Flexible Cords and Cables"
c(UL) approved to meet CSA standard C22.2, flexible cords

Application: Portable power tools, light duty motors, lighting, and temporary electric power

All trademarks are property of their respective owners. All specifications are subject to change.

| Revision History | | |
|------------------|-------------------|----------------------|
| 00 | 2019/10/09 | Initial release |
| 01 | 2019/11/20 | Added P/N to Table 1 |
| Created L. Jian | Approved A. Huang | |

Bristol | Unit 61, Gazelle Rd., Weston Industrial Estate, Weston-super-Mare, North Somerset BS24 9ES UK

Frankfurt | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf

Milwaukee | 5001 South Towne Dr. New Berlin, WI 53151 USA

Suzhou | B2-2 Weiting Town Industrial - Workshop A, No. 9 Weixin Rd., Suzhou Industrial Park. Jiangsu, China 215122