

**1. CONDUCTOR:**

- 1.1 Size and Material: 12 19/.0185" AWG bare copper wire.
- 1.2 O.D.: .089" nom.

**2. INSULATION:**

- 2.1 Extruded ETFE.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .115" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 300 VAC R.M.S.
- 3.2 Temperature rating: 150°C


**4. REFERENCES:**

- 4.1 UL Subject 758 (AWM), Style 1643.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I, Group A.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Daniel Curson</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com					
								Date: November 12, 2019							
								Verified: <i>Carrie Lott</i>		Description: <b>XTF13B1219/0185-X</b>					
								Date: November 12, 2019							
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.								Size: <b>A</b>		Scale: ---		Page: 1 of 1		Code Ident. No: <b>57104</b>	Specification No.: <b>Q04645-X</b>