

## **Specification Sheet**

Part Number: 169-60020



Article Number	169-60020
Туре	CTN340
Color	Black with Gray Stripe (BKSTGY)
Features & Benefits	• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture • Tubing protects cables and wires against automotive fluids, vibration wear • Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight
Quantity Per	box
Product Description	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness

and sunlight on cables and wires.

assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold

Short Description	Convoluted Tubing, Slit, .75" Dia, PA6, Black with Gray Stripe, 100 ft/pkg
Global Part Name	CTN340-PA6-BK
Technical Description	Convoluted Tubing, Slit, 3/4" Dia., PA6, Black w/Gray Stripe
Length L (Imperial)	100.0
Length L (Metric)	30.5
Variant	Slit
Inner Diameter D (Imperial)	0.759
Inner Diameter D (Metric)	19.28
Diameter D (imperial)	0.989
Diameter D (metric)	25.12
Outside Diameter OD(Imperial)	0.989
Outside Diameter OD(metric)	25.12
Nominal Diameter (Imperial)	3/4
Nominal Diameter (Metric)	19.05
Wall Thickness WT (Imperial)	0.005
Wall Thickness WT (Metric)	0.127

Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL 94 HB
Halogen free	No
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	3926909988

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

<sup>© 2019</sup> HellermannTyton. All Rights Reserved.