THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PREMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS							
REV	DESCRIPTION	DATE	APPROVED				
A	APPROVED FOR PRODUCTION	11/7/00	D. PARHAM				

CATEGORY FIVE SCREENED TWISTED PAIR CABLE

(SUPPLIED IN 1000-FOOT REELS)

GENERAL DESCRIPTION: CATEGORY 5 SHIELDED PATCH CABLE. CABLE IN THIS FAMILY CONSISTS OF TWISTED PAIRS OF STRANDED COPPER 26AWG (7X34) CONDUCTORS WITH AN OVERALL ALUMINIZED POLYESTER FOIL SHIELD AND STRANDED 26AWG TINNED COPPER DRAIN WIRE. THE OUTER JACKET IS GRAY PVC. RATED AS U.L. LISTED COMMUNICATIONS CABLE, TYPE CM. TEMPERATURE RATING: 75°C.

PART NUMBER OF PAIRS TFC2002 2

ELECTRICAL CHARACTERISTICS:

CONDUCTOR D.C. RESISTANCE, 20°C (MAX.): 44.4Ω/1,000 FEET

CAPACITANCE (NOM.): 14 PF/FOOT

CHARACTERISTIC IMPEDANCE, 1-100 MHz (NOM.): 100Ω

DELTA DELAY (SKEW)(MAX.)

2-PAIR: 0.15 NSEC/METER

ATTENUATION AND CROSSTALK (NEXT)

FREQUENCY	ATTENUATION	CROSSTALK
(MHz)	DB/1000' (NOM.)	<u>DB/1000′</u>
.256	5.7	_
.772	8.2	64
1.0	8.65	62
25.0	38.0	41
100.0	85.8	32

COLOR CODES: PAIR 1 ORANGE, WHITE WITH ORANGE

PAIR 2 GREEN, WHITE WITH GREEN

	L-com			45 BEECHWOOD DRIVE NORTH ANDOVER, MA			
	DRAWING TITLE						
		CAT: 5 BULK CABLE					
DRAWN BY B. DAGGETT	DATE 11/2/00	SIZE DRAWING NO. A TFC2002			2002	REV.	
APPROVED BY D. PARHAM	DATE 11/7/00	SCALE				SHE	ET 1 OF 1