


## TECHNICAL DATA SHEET

### Diagram



### Description

Cable Part Code*	YJ72448
Cable Type	10PR10AWG NYLON TC 600V,for indoor application
Reference Standards	UL 1277 TC-ER, JB/T 10261

### Conductor

Conductor Material	Stranded Bared Copper
Conductor Size	10AWG

### Insulation

No. of Cores/Pair/Triad/Quad	10 Pairs
Insulation Material	PVC + NYLON (UL83 THHN/THWN) WET RATED
Nom. Insulation Diameter(mm)	4.4
Insulation Color Code	1.Black*Brown 2.Black*Red 3.Black*Orange 4.Black*Yellow 5.Black*Green 6.Black*Blue 7.Black*Violet 8.Black*Gray 9.Black*White 10.Black*Pink
Water Block Tape	YES

### Shielding

Shielded/Unshielded	Unshielded
---------------------	------------

### Outer Jacket/Sheath Material

Outer Jacket Material	PVC
Nom. Overall Diameter(mm)	33.5

### Physical/Mechanical Properties

Temperature Range	-30~90°C (Cable)
Nom. Cable Weight (kg/km)	1572

### Electrical Properties

Voltage Rating (V)	600V
Max. Conductor Resistance @20°C (Ω/km)	3.41

\*Ordering stock code will be created at the time of placing the order and the stock code will include cable part code, outer jacket color & putup length.

© 2016 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.