

16/3 Type SJ00W 105C Yellow




PRODUCT DATA SHEET

This cable is suitable for control equipment on machine tools subjected to medium mechanical stresses; for fixed or flexible installation, where free movement is required without tensile stresses and without forced guidance system; and in dry, damp and wet interiors— including water-oil mixtures.

Design Number 10215
Part Number 32121709
Customer Number N/A

CONSTRUCTION

Conductor: Stranded bare copper,
Conductor Size: 16AWG(65/34)
Insulation: EPDM, oil resistant
Insulation Avg. Thickness: 0.030"(Nom.)
Insulated Conductor O.D.: 0.124"(Nom.)
Filler: PP rope
Separator: Paper
Jacket Material: CPE, oil resistant
Jacket Avg. Thickness: 0.030"(Nom.)
Overall Diameter: 0.330"(Nom.)
Jacket Color: Yellow
Print Legend:
ASCENT #32121709 E486041 16AWG 3/C SJ00W (UL) 300V (-40 - 105C)--
CSA LL268042 FT-2 WATER RESISTANT P-07KA140001-MSHA --RoHS xxxx FT



Color Code: 1. Black 2. White 3. Green

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): -40°C to +105°C
Operating Voltage: 300V
Flame Test : CSA FT2

SAFETY CHARACTERISTICS

RoHS Compliance: European Directive 2015/863/EU
Approvals: UL Flexible Cord, Subject 62
CSA Flexible Cord, C22.2 No.49
MSHA Approved

Application: Machine tools, power tools, portable machinery, submersible pumps, motor leads

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2019/02/21	Initial release
Created L. Jian	Approved A. Huang	

Bristol | Unit 61, Gazelle Rd., Weston Industrial Estate, Weston-super-Mare, North Somerset BS24 9ES UK
Frankfurt | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf
Milwaukee | 5001 South Towne Dr. New Berlin, WI 53151 USA
Suzhou | B2-2 Weiting Town Industrial - Workshop A, No. 9 Weixin Rd., Suzhou Industrial Park, Jiangsu, China 215122

