

# SECURITY ALARM CABLE | RISER UNSHIELDED



AWG	COND	STRAND	PART NO.	CAP pF/FT	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
					INCH	mm	INCH	mm	
22	2	SOL	82202GY	28	.015	.38	.122	3.10	9
	2	7	12202R	28	.015	.38	.118	3.00	10
	3	7	12203R	28	.015	.38	.125	3.18	15
	4	SOL	82204GY	28	.015	.38	.141	3.58	16
	4	7	12204R	28	.015	.38	.136	3.45	19
	6	7	12206R	28	.015	.38	.162	4.11	27
	8	7	12208R	28	.015	.38	.176	4.47	30
	10	7	12210R	28	.015	.38	.198	5.03	41
20	2	7	12002R	30	.015	.38	.134	3.40	15
	4	7	12004R	30	.015	.38	.155	3.94	23
18	2	7	11802R	29	.015	.38	.161	4.09	20
	3	7	11803R	29	.015	.38	.171	4.34	26
	4	7	11804R	29	.015	.38	.188	4.78	32
	5	7	11805R	29	.015	.38	.199	5.05	41
	6	7	11806R	29	.015	.38	.226	5.74	48
	7	7	11807R	29	.015	.38	.226	5.74	52
	8	7	11808R	29	.015	.38	.243	6.17	59
	9	7	11809R	29	.015	.38	.256	6.50	66
	10	7	11810R	29	.015	.38	.280	7.11	74
	12	7	11812R	29	.015	.38	.291	7.39	90
16	2	19	11602R	33	.015	.38	.184	4.67	28
	3	19	11603R	33	.015	.38	.196	4.98	38
	4	19	11604R	33	.015	.38	.216	5.49	51
14	2	19	11402R	34	.015	.38	.224	5.69	39
	3	19	11403R	34	.015	.38	.239	6.07	56
	4	19	11404R	34	.015	.38	.264	6.71	73
12	2	19	11202R	38	.015	.38	.262	6.65	57

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to [www.adcable.com](http://www.adcable.com) for the most up to date information. Rev 0419

## PRODUCT DESCRIPTION

PVC insulated stranded bare copper conductors, twisted with an overall gray PVC jacket\* with rip cord.

## APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

## SPECIFICATIONS

**Conductor** Bare Copper

### Insulation

- 22 AWG .007"
- 20 AWG .008"
- 18-16 AWG .010"
- 14-12 AWG .012"

**Jacket** PVC

### NEC Articles

- 22-16 AWG: FPLR/760, CMR/800, CL3R, CL2R/725
- 14-12 AWG: FPLR, CL3R

**Voltage Rating** 300 V

**Temp. Rating** -25°C to 75°C

## COLOR CODE CHART

Cond	Color	Cond	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

## AVAILABLE PUT-UPS

1,000' Reels and Boxes

500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

## CABLE IDENTIFICATION

XX AWG XC (UL) TYPECL3R/  
FPLR c(UL)us TYPE CMR  
E179335

\*14-12 AWG are not recognized by c(UL) or c(ETL).

\*Other colors available upon request.

Please consult factory for minimums and lead times.



(800) 343 2579 • [www.adcable.com](http://www.adcable.com)