

SECURITY ALARM CABLE | PLENUM UNSHIELDED



AWG	COND	STRAND	PART NO.	CAP pF/FT	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
					INCH	mm	INCH	mm	
22	2	SOL	982202	31	.018	.45	.118	3.00	9
	2	7	912202	31	.015	.38	.116	2.95	12
	3	7	912203	31	.015	.38	.123	3.12	15
	4	SOL	982204	31	.018	.45	.136	3.45	16
	4	7	912204	31	.015	.38	.134	3.40	19
	6	7	912206	31	.015	.38	.158	4.01	24
	8	7	912208	31	.015	.38	.169	4.24	30
	10	7	912210	31	.015	.38	.186	4.72	37
20	12	7	912212	31	.015	.38	.200	5.08	42
	2	7	912002	33	.015	.38	.138	3.51	15
	3	7	912003	33	.015	.38	.143	3.63	21
	4	7	912004	33	.015	.38	.160	4.06	24
18	2	7	911802	34	.015	.38	.157	3.99	22
	3	7	911803	34	.015	.38	.168	4.27	28
	4	7	911804	34	.015	.38	.186	4.72	36
	5	7	911805	34	.015	.38	.203	5.16	41
	6	7	911806	34	.015	.38	.211	5.36	51
	8	7	911808	34	.015	.38	.242	6.15	65
	9	7	911809	34	.015	.38	.256	6.50	68
	10	7	911810	34	.015	.38	.260	6.60	75
16	12	7	911812	34	.015	.38	.283	7.19	89
	2	19	911602	38	.015	.38	.180	4.57	26
	3	19	911603	38	.015	.38	.191	4.85	38
14	4	19	911604	38	.015	.38	.211	5.36	47
	2	19	911402	39	.015	.38	.222	5.64	40
12	3	19	911403	39	.015	.38	.236	5.99	60
	4	19	911404	39	.015	.38	.261	6.63	75
12	2	19	911202	42	.015	.38	.257	6.53	58
	4	19	911204	42	.015	.38	.312	7.93	108

PRODUCT DESCRIPTION

Low smoke PVC insulated stranded bare copper conductors, twisted with an overall low smoke white PVC jacket* with rip cord.

APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

SPECIFICATIONS

Conductor Bare Copper

Insulation Low Smoke PVC

- 22 AWG .007" PVC
- 20 AWG .008" PVC
- 18 AWG .009" PVC
- 16 AWG .010" PVC
- 14-12 AWG .012" PVC

Jacket Low Smoke PVC

NEC Articles

- 22-16 AWG: FPLP/760, CMP/800, CL3P, CL2P/725
- 14-12 AWG: FPLP, CL3P

Voltage Rating 300 V

Temp. Rating -25°C to 75°C

COLOR CODE CHART

Cond	Color	Cond	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

AVAILABLE PUT-UPS

1,000' Reels and Boxes

500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

XX AWG XC (UL) TYPE CL3P/
FPLP c(UL)us TYPE CMP E179335

*Other colors available upon request. Please consult factory for minimums and lead times.

*14-12 AWG are not recognized by c(UL).

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to www.adcable.com for the most up to date information. Rev 0419



(800) 343 2579 • www.adcable.com