



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 87-2038

CONSTRUCTION SPECIFICATIONS

Description	8 Pair 20 AWG OS 300V CSA Instrumentation/Tray Cable (LSZH)
Conductor	20 AWG 19 Strand Tinned Copper
Conductor Diameter	0.040"
Insulation Type	Cross Linked Polyethylene (XLPE)
Insulation Thickness	0.020"
Cable Assembly	Conductors are paired and then cabled together with an overall shield and drain.
Pair Identification	Black & White Number Coded
Drain Wire	22 AWG 7 Strand Tinned Copper - Concentric
Shielding Tape	Aluminum/laminate
Ripcord	Ripcord included under the cable jacket
Jacket	Flame Retardant Polyethylene (Low Smoke Zero Halogen)
Jacket Thickness	0.060" (minimum average)
Overall Cable Diameter	0.589"
Jacket Print	DECA 8PR 20 AWG SHIELDED 300V CSA TYPE CIC TC 90C WET/90C DRY XLPE SUN RES DIRECT BURIAL -25C FT4-ST1 LL83251 ---- ROHS HALOGEN FREE work order #, month, year, meter markings (every 1 metre)

ELECTRICALS

Voltage	300V
Conductor Resistance	9.2 Ohms/Mft @20C
Capacitance	14 pF/ft
Characteristic Impedance	115 Ohms

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	CSA C22.2 No. 230, Tray Cables CSA C22.2 No. 239 Control and Instrumentation Cables
Applications	Class I, Zone 2, Division 2
Flame Test Rating	CSA FT4
Temperature Rating	-25C to 90C Wet/90C Dry
Cable Weight	228 kg/km
Copper Content	83 kg/km
Max Pull Tension	97 kgs
Min Bending Radius	4.75 inches (installed)
Nominal Cable Length	3,000 metres
Min Installation Temp	-25C

Rev. 004

18-Dec-13