



Manufactured By:
 134 Ferry St.
 South Grafton, Ma 01560
 www.huesonwire.com

Issue Date: 3/3/2020

Issue: 1

Construction

Description: 3/C 22 7/30 TC PVC/PVC		Diam. (In)
Component:	3 Conductors	
Conductor:	22 AWG 7/30 Tinned Copper to ASTM-B33	
Insulation:	0.01" Premium Grade PVC	0.050" +/- .003"
Color Code:	Red, Black, Green	
Cable Assembly:	Bunch Cable 3 Conductors	
Binder:	Tissue Paper Separator	
Jacket:	0.03" Flexible PVC, Oil, Moisture UV Resistant, VW-1	
Jacket Color:	Black	0.170" +/- 0.010"
Print:	E174416 RU AWM 2661 105C 300V VW-1 --- cRU AWM I/II A/B 105C 300V FT-1	
Specifications:	<u>AWM Style</u>	<u>Temp</u>
UL	AWM-2661	105°C
Canadian cRU	cRU	105°C
	<u>Voltage</u>	<u>Flame</u>
	300	VW-1
	300	FT-1
Environmental Compliance		
<ul style="list-style-type: none"> • RoHS EU Directive 2011/65/EU (1&2&3) • REACH Regulation 201: • California Prop 65: 		
		IQ-20039

Per Tony Cuz on 3/3/20, Approved.



Issue Date: 3/3/2020
Issue: 1

Drawing/Rotation:

