

1. CONDUCTOR:

- 1.1 Size and Material: 20 19/32 AWG silver-plated copper wire.
- 1.2 O.D.: .038" nom.

2. INSULATION:

- 2.1 Extruded special ETFE (Tefzel® 750).
- 2.2 Print on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .058" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

3. PERFORMANCE:




- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C

4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 10086.
- 4.2 CSA Standard C22.2 No.210.2-M90 (AWM), Class I Group A/B.

CUSTOMER APPROVAL

Sign: _____
 Date: _____

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: 		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com		
								Date: May 28, 2003				
								Verified: 		Description: XTL10S2019/32-X		
								Date: May 29, 2003				
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F00464-X