

UL CMR/2464 20AWG/9C, Black



PRODUCT DATA SHEET

Cable is suitable for installation under NEC (NFPA 70) article 800 guidelines.
Cable is suitable for installation in Canada under Section 60 of CEC, Part I.
Internal wiring or external interconnection of electronic equipment.


Design Number 10423
Part Number 32130998
Customer Number N/A

CONSTRUCTION

Conductor: Stranded tinned copper
Conductor Size: 20AWG(7/28)
Insulation: Polyvinyl Chloride
Insulation Thickness: 0.013"(Nom.)
Insulation Diameter: 0.064"(Nom.)
Cable Lay Length: 3.50"(Nom.)
Jacket Material: Polyvinyl Chloride
Jacket Thickness: 0.032"(Nom.)
Overall Diameter: 0.296"(Nom.)
Jacket Color: Black

Print Legend (Footage Markers):

ASCENT E478021 20AWG 9C 75C C(UL)US TYPE CMR SUN RES FT4 OR
AWM 2464 300V 80C "ROHS COMPLIANT" MADE IN USA



Color Code: Black, White, Red, Green, Brown, Blue, Orange
Yellow, Purple

ELECTRICAL CHARACTERISTICS

Operating Temperature (°C): 80°C
Operating Voltage: 300V
Weight: 61 Lbs/Mft
Flame Test: Cable meets (UL) 1685 (Vertical)

SAFETY CHARACTERISTICS

Approvals: UL AWM Style 2464 per UL standard 758
(UL)US listed as CMR per UL standard 444 and per CSA C22.2 No. 214-17
RoHS Compliant: European Directive 2015/863/EU
REACH Compliant: Regulation (EC) No 1907/2006 Updated Jan.15,2019

Application: Internal wiring or external interconnection of electronic equipment

All trademarks are property of their respective owners. All specifications are subject to change.

Revision History		
00	2020/10/19	Initial Release
Created L. Jian	Approved A. Huang	

Bristol | Unit 61, Gazelle Rd., Weston Industrial Estate, Weston-super-Mare, North Somerset BS24 9ES UK
Frankfurt | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf
Milwaukee | 5001 South Towne Dr. New Berlin, WI 53151 USA
Suzhou | B2-2 Weiting Town Industrial - Workshop A, No. 9 Weixin Rd., Suzhou Industrial Park, Jiangsu, China 215122

