

## ALPHA WIRE

Part Number: 19-2698

Issue:

B

Page 1 of 1 Pages

Issue Date:

3/23/2020

### Cable Specification

<u>Component 1</u>	6 COND
<u>Conductor:</u>	18 (41/34) AWG TC
<u>Insulation:</u>	0.012" Wall, Nom. MPPE
Color Code:	6 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED
<u>Component 2</u>	2 PAIR
<u>Conductor:</u>	18 (41/34) AWG TC
<u>Insulation:</u>	0.012" Wall, Nom. MPPE
Color Code:	4 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED
<u>Pair:</u>	2/Cond Cabled Together
<u>Final Assembly</u>	2 Components
Core Wrap:	NWP Tape, 25% Overlap, Min.
<u>Shield:</u>	APA Foil Tape, 25% Overlap, Min.
Drain Wire:	18 (41/34) AWG TC
Braid:	TC,85% Coverage, Min.
<u>Jacket:</u>	0.032" Wall, Nom., PUZH
Jacket OD:	0.377"
Jacket Color:	BLACK

### Approvals

UL:	AWM/STYLE 21959
	60C OIL
	SUNRES
CSA:	c(RU) AWM I/II A/B
	FT2
MIL:	NONE
CE Compliant:	YES
ROHS Compliant:	YES
REACH Compliant:	NO

### Miscellaneous

Temperature:	90 C
Voltage:	600 V <sub>RMS</sub>
Put Ups:	1000 FT PUTUP
Requested Quantity:	1000Ft., 2000Ft., 5000Ft.

### Application Notes

Color Code:  
2/PR - Black-White, Gray-Violet  
6/C - TBD

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

### PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.