



Issue Date: 4/14/2020

Issue: 1

Construction

Description: 4/C 22 19/34 BC PVC/PVC		Diam. (In)
Component:	4 Conductors	
Conductor:	22 AWG 19/34 Bare Copper to ASTM B-174	0.034 "
Insulation:	0.013" Premium Grade PVC 0.0597 +/- .003"	0.060 "
Color Code:	Red, Blue, Red/White, Blue/White	0.060 "
Cable Assembly:	Bunch Cable 4 Conductors	0.144 "
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.144 "
Binder:	Non-Woven Polyester or Clear Mylar Tape Binder	0.148 "
Jacket:	0.031" Flexible PVC, Oil, Moisture UV Resistant, VW-1	0.210 "
Jacket Color:	White 0.21 +/- 0.010"	0.210 "
Print:	E174416 RU AWM 20811 105C 600V OR 2661 105C 300V VW-1 --- cRU AWM I/II A 105C	
Indent	600V FT-1	

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>	
UL	AWM-2661	105°C	300	VW-1	
	AWM-20811	105°C	600	VW-1	
Canadian cRU	AWM	105°C	300	FT-1	I/II A/B

Designed for UL Standard 1598 Clause 6.9.3 AWM Cables for use in the USA

Environmental Compliance	
<ul style="list-style-type: none"> • RoHS EU Directive 2011/65/EU (1&2&3) • REACH Regulation 205: • California Prop 65: 	IQ-20219



Issue Date: 4/14/2020
Issue: 1

Drawing/Rotation:

