



Manufactured By:
 134 Ferry St.
 South Grafton, Ma 01560
 www.huesonwire.com

Issue Date: 1/7/2020

Issue: 1

Construction

Description: 4/C 18 16/30 TC PVC/PVC		Diam. (In)
Component:	4 Conductors	
Conductor:	18 AWG 16/30 Tinned Copper to ASTM B-174	
Insulation:	0.01" Premium Grade PVC	0.067" +/- .003"
Color Code:	White, Black, Brown, Blue	
Cable Assembly:	Bunch Cable 4 Conductors	
Separator:	Tissue Paper Separator	
Jacket:	0.03" Flexible PVC, Oil, Moisture UV Resistant, VW-1	
Jacket Color:	Black	0.226" +/- 0.010"
Print:	E174416 RU AWM 2661 105C 300V VW-1 --- cRU I/II A 105C 300V FT1	

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
UL	AWM-2661	105C	300	VW-1
Canadian cRU	2661	105C	300	FT-1

Environmental Compliance	
<ul style="list-style-type: none"> • RoHS EU Directive 2011/65/EU (1&2) • REACH Regulation 169: • California Prop 65: 	IQ-190530



Issue Date: 1/7/2020
Issue: 1

Drawing/Rotation:

