



Hueson Wire
 134 Ferry St.
 South Grafton, Ma 01560
 www.huesonwire.com

Issue Date: 4/20/2020

Construction

Issue: 1

Description: 6/C 26 7/34 TC PVC/PVC		Diam. (In)
Component:	6 Conductors	
Conductor:	26 AWG 7/34 Tinned Copper to ASTM B-8	0.019 "
Insulation:	0.0094" Premium Grade PVC 0.0378 +/- .003"	0.038 "
Color Code:	Black, Green, Red, Blue, Orange, Yellow	0.038 "
Cable Assembly:	Bunch Cable 6 Conductors	0.113 "
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.113 "
Binder:	Non-Woven Polyester or Clear Mylar Tape Binder	0.117 "
Jacket:	0.0215" Flexible PVC, Oil, Moisture UV Resistant, VW-1	0.160 "
Jacket Color:	Gray 0.16 +/- 0.010"	0.160 "
Print: E174416 RU 80C 300V VW-1 --- cRU I/II A 105C 300V FT1		

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
UL	AWM	80°C	300	VW-1
Canadian cRU	AWM	80°C	300	FT-1 I/II A/B

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2&3)
- REACH Regulation 205:
- California Prop 65:

IQ-20237