



Hueson Wire
 134 Ferry St.
 South Grafton, Ma 01560
 www.huesonwire.com

Issue Date: 2/22/2020

Issue: 1

Construction

Description: 2/C 22 7/30 TC PVC/PVC		Diam. (In)
Component:	2 Conductors	
Conductor:	22 AWG 7/30 Tinned Copper to ASTM-B33	0.030 "
Insulation:	0.01" Premium Grade PVC 0.05 +/- .003"	0.050 "
Color Code:	Blue and Red or Black and Red	0.050 "
Cable Assembly:	Bunch Cable 2 Conductors	0.100 "
Binder:	Non-Woven Polyester or Clear Mylar Tape Binder	0.104 "
Jacket:	0.032" Flexible PVC, Oil, Moisture UV Resistant, VW-1	0.168 "
Jacket Color:	White 0.168 +/- 0.010"	0.168 "

Print: E174416 RU AWM 2661 105C 300V VW-1 --- cRU I/II A 105C 300V FT1

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
UL	AWM-2661	105°C	300	VW-1
Canadian cRU	AWM	105°C	300	FT-1 I/II A/B

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2&3)
- REACH Regulation 205:
- California Prop 65:

IQ-20110