


# Feedback Cable Assemblies for continuous flexing

According to Allen-Bradley 2090 standard



## Application

- Servo feedback cables for Allen-Bradley drives
- Due to optimized cable construction optimally suited for continuous flexing applications in C-tracks
- Very good resistance against aggressive coolants and lubricants
- Especially for industrial environments in machines and plants

## Characteristics

- High active and passive interference resistance (EMC)
- Silicone free
- RoHS compliant

## Technical data

Rated voltage $U_N$	1000 V 80 °C
Temperature range fixed	-40 °C ... +80 °C
Temperature range moving	-25 °C ... +80 °C
Minimum bending radius fixed	6×D
Minimum bending radius moving	12×D
Burning behavior according to	IEC 60332-1 VDE 0482 Part 265-2 UL 1581 Part 1080 VW-1 UL FT1
Halogen free according to	EN 50267-2-1
Certifications	cULus UL AWM 21223

## Construction

- Conductor: CU-wire bare
- Conductor category: Superfinely stranded DIN VDE 0295, IEC 60228, Class 6
- Conductor marking: Color coded
- Ground conductor green/yellow according to DIN EN 50334  
G = with green/yellow ground conductor, × = without ground conductor
- Control pair:
- Overall stranding: conductors layered construction
- Overall wrapping: Fleece taping, over the cable core
- Overall shield: Braid shield, Tinned copper wires, optical cover approx. 85%
- Jacket material: PUR
- Surface: matt, adhesion-free
- Jacket color: green RAL 6018

Part No.	Allen-Bradley designation*	Cable length m	Number of conductors/ cross-section	Outer Ø mm
<b>Base cable SpeedTec</b>				
193977.1000	2090-CFBM7DF-CEAF10	10.0	(5×2×AWG22)	9.2
193958.1000	2090-CFBM7DF-CDAF10	10.0	(2×AWG16+2×AWG22+ 6×2×AWG26)	10.8
193350.1000	2090-CFBM7DD-CEAF10	10.0	(5×2×AWG22)	9.2
<b>DIN thread</b>				
193973.1000	2090-CFBM4DF-CDAF10	10.0	(2×AWG16+2×AWG22+ 6×2×AWG26)	10.8
<b>Extension SpeedTec</b>				
193979.1000	2090-CFBM7E7-CEAF10	10.0	(5×2×AWG22)	9.2
193978.1000	2090-CFBM7E7-CDAF10	10.0	(2×AWG16+2×AWG22+ 6×2×AWG26)	10.8

\*Allen-Bradley, Kinetix®, and 2090 series article designations are trademarks of Rockwell Automation, Inc. and are for reference purposes only.  
\* UL approval and technical data shown apply to the cable used in the assemblies.  
The product photos are not to scale and do not represent detailed images of the respective products.  
Specifications are subject to change without prior notice.