



711 Lidgerwood Avenue
Elizabeth, NJ 07207-0711 USA
1-908-925-8000
1-800-52 ALPHA
www.alphawire.com

Part Number: 20-1393
Page 1 of 1 Pages

Issue:
Issue Date: 6/10/2020

Cable Specification

Component 1 3 COND
 Conductor: 16 (26/30) AWG BC
 Insulation: 0.022" Wall, Nom. PVC
 Color Code: 2 SOLID COLORS/ 1 STRIPED/ 2 NUMBER CODED

Final Assembly 3 Components
 Core Wrap: NWP Tape, 25% Overlap, Min.
 Jacket: 0.036" Wall, Nom., PVC
 Jacket OD: 0.300"
 Jacket Color: SLATE

Approvals

 UL: AWM/STYLE 2586
 CSA: c(RU) AWM I/II A/B
 FT1
 MIL: NONE
 CE Compliant: YES
 ROHS Compliant: YES
 REACH Compliant: YES

Miscellaneous

 Temperature: 105 C
 Voltage: 600 V_{RMS}
 Put Ups: 1000 FT PUTUP
 Requested Quantity: 1000Ft.

Application Notes

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR
MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.