



**RADIX WIRE**  
**BRAIDLESS SILICONE RUBBER**  
**HIGH TEMPERATURE LEAD WIRE**

150°C 600 Volt  
 UL 3213 / CSA AWM I A/B FT2

Part Number	AWG	Stranding	Conductor Type	Insulation Mil Wall (In.)	Nominal Diameter (In.)	Approx. LBS. / Mft.
HDA06T105-MR01-E4S07	6	1050/.0050" (7 X 150)	Tinned Copper	0.063"	0.331"	107

- Due to the high strand count and the use of silicone rubber as the insulation system, this product is suitable for use in high flex applications.
- **Color:** Green with two yellow longitudinal stripes
- **Bend Radius:** 6 times the diameter of the cable

All Dimensions are Nominal

All material included in this bulletin is advisory only and its use by anyone is entirely voluntary. Information herein is believed to be accurate as of publication date, however, if errors exist they are unintentional and Radix is not responsible for any claim traceable to such an error. Reliance upon the contents of this bulletin for any purpose by anyone is at the sole risk of that person and Radix Wire Co. Inc. is not responsible for any loss, Claim or damage arising therefrom. Information contained in this bulletin is subject to change without notice. All users are cautioned that any UL or CSA approvals referenced in this publication may be revised or withdrawn at any time. Interested persons may receive current information concerning the status of any listing by contacting the appropriate listing body: UL or CSA.