

1. CONDUCTOR:

- 1.1 Size and Material: 6 133/27 AWG tin-plated copper wire.
- 1.2 O.D.: .206" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Marking on insulation: as per UL and CSA Standards.
- 2.3 O.D.: .326" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).
- 2.5 Talc powder applied on the insulation.

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 150°C






4. REFERENCE:

- 4.1 UL Subject 758 (AWM), Style 3213.
- 4.2 CSA Standard C22.2 No. 210.2-M90 (AWM), Class I, Group A.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.							 <p>This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: 		 <p>1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com</p>			
1173								Date: September 14, 2004					
								Verified: 		Description: XSF60Z6133/27-X			
								Date: September 14, 2004					
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								 <p>A member of The Marmon Group of companies</p>	Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F01502-X