


HOOK-UP WIRE



CSA TEW



Description:

Stranded Tinned Copper, Color Coded Polyvinylchloride Insulation, .032" Nominal Insulation Thickness

Characteristics:

Temperature Rating: -40°C to +105°C Voltage Rating: 600V Passes UL VW-1 Flame Test

WEICO NO.	CONDUCTOR		NOM. O.D. (IN)
	SIZE	STRAND	
3224	24	7/32	.088
3222	22	7/30	.095
3220	20	10/30	.102
3218/1	18	Solid	.104
3218	18	16/30	.112
3216	16	26/30	.125
3214	14	41/30	.142
3212	12	65/30	.156
3210	10	105/30	.184
3208 *	8	133/29	.265
3206 **	6	133/27	.341
3204 **	4	133/25	.388

*UL 1028, .047" wall thickness

**UL 1283, .063" wall thickness

COLORS:

0 - Black, **1** - Brown, **2** - Red

3 - Orange, **4** - Yellow, **5** - Green

6 - Blue, **7** - Violet, **8** - Gray, **9** - White

X Denotes 0 - 9 color coding

STRIPES:

Any of the above colors are available in any combination of stripes up to a maximum of three stripes.

Standard Put-Ups: 100 ft., 1000 ft.