

# 12/3 Type SJOOW Black, without Filler/Separator



PRODUCT DATA SHEET

This cable is suitable for control equipment on machine tools subjected to medium mechanical stresses; for fixed or flexible installation, where free movement is required without tensile stresses and without forced guidance system; and in dry, damp and wet interiors— including water-oil mixtures.


**Design Number** 10534  
**Part Number** 32164937  
**Customer Number** N/A

## CONSTRUCTION

**Conductor:** Stranded bare copper, Class K per ASTM B-174  
**Conductor Size:** 12AWG(65/30)  
**Insulation:** EPDM, oil resistant  
**Insulation Avg. Thickness:** 0.030"(Nom.)  
**Insulated Conductor O.D.:** 0.157"(Nom.)  
**Jacket Material:** CPE, oil resistant  
**Jacket Avg. Thickness:** 0.045"(Nom.)  
**Overall Diameter:** 0.437"(Nom.)  
**Jacket Color:** Black

### Print Legend:

ASCENT E486041 12AWG 3/C SJOOW (UL) 300V (- 40-90C)-- CSA LL268042  
FT-2 WATER RESISTANT P-07KA140001-MSHA --RoHS xxxxxFT



**Color Code:** 1. Black 2. White 3. Green

## ELECTRICAL CHARACTERISTICS

**Operating Temperature (°C):** -40°C to +90°C  
**Operating Voltage:** 300V  
**Flame Test :** CSA FT2

## SAFETY CHARACTERISTICS

**RoHS Compliance:** European Directive 2015/863/EU  
**Approvals:** UL Flexible Cord, Subject 62  
CSA Flexible Cord, C22.2 No.49  
MSHA Approved

**Application:** Machine tools, power tools, portable machinery, submersible pumps, motor leads

*All trademarks are property of their respective owners. All specifications are subject to change.*

Revision History		
00	2021/09/15	Initial release
01	2022/05/24	Part Number added
Created L. Jian	Approved A. Huang	

**UK HQ** | Unit 11, Humphrys Road, Woodside Industrial Estate, Dunstable, LU5 4TP UK  
**Frankfurt** | Rudolf-Braas-Strasse 2, D-61381 Friedrichsdorf  
**Milwaukee** | 5001 South Towne Dr. New Berlin, WI 53151 USA  
**Suzhou** | B2-2 Weiting Town Industrial - Workshop A, No. 9 Weixin Rd., Suzhou Industrial Park. Jiangsu, China 215122

