


Braidless Silicone Rubber

150° C., 10 to 50kV DC



- A. Center conductor- solid or stranded tin-plated copper
- B. Insulation- extruded silicone rubber

Applications

Internal wiring of electrical equipment and appliances where totally enclosed.

Listings

150° C., 10 to 50 kV DC: UL 3239

	Catalog Number	Size (AWG)	Stranding (No./AWG)	Insulation Thickness (mils)	Overall Diameter (inches)	Weight (lbs/1000 ft)	Part Number	
							U.S.	Canada
10 kV	BSR3239-2210	22	7/30	40	.110	7	-	H300
	BSR3239-2010	20	10/30	40	.117	9	-	H301
15 kV	BSR3239-2215	22	7/30	45	.120	8	-	H302
	BSR3239-2015	20	10/30	45	.127	10	-	H303
	BSR3239-1815	18	16/30	45	.135	12	-	H304
	BSR3239-1615	16	26/30	45	.146	16	-	H305
	BSR3239-1415	14	41/30	45	.160	22	-	H306
	BSR3239-1215	12	65/30	45	.180	31	-	H307
	BSR3239-1015	10	105/30	45	.214	44	-	H308
	20 kV	BSR3239-2220	22	7/30	50	.130	9	-
BSR3239-2020		20	10/30	50	.137	11	-	H312
25 kV	BSR3239-2225	22	7/30	62	.154	12	-	H313
	BSR3239-2025	20	10/30	62	.161	14	-	H314
	BSR3239-1825	18	16/30	62	.169	17	-	H315
	BSR3239-1625	16	26/30	62	.180	21	-	H316
	BSR3239-1425	14	41/30	62	.194	27	-	H317
	50 kV	BSR3239-2240	22	7/30	97	.224	24	-
BSR3239-2040		20	10/30	97	.231	26	-	H324
BSR3239-1840		18	16/30	97	.239	29	-	H325
BSR3239-1640		16	26/30	97	.250	34	-	H326
BSR3239-1440		14	41/30	97	.264	41	-	H327
BSR3239-1240		12	65/30	97	.284	52	-	H328
BSR3239-1040		10	105/302	97	.318	69	-	H329

All figures referenced are nominal.



Harbour
INDUSTRIES

802-985-3311 U.S.