

1. CONDUCTOR:

- 1.1 Size and Material: 14 41/30 AWG tin-plated copper wire.
- 1.2 O.D.: .072" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Wall thickness: .140" nom.
- 2.3 Marking on the insulation: as per UL Standard.
- 2.4 O.D.: .352" nom.
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).
- 2.6 Talc powder applied on the insulation.

3. PERFORMANCE:

- 3.1 Voltage rating: 50 KVDC
- 3.2 Temperature rating: 150°C


4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 3239.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Daniel Curson</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com		
						Date: November 1, 2018						
						Verified: <i>David Lott</i>		Description: XSF140Z1441/30-X				
						Date: November 1, 2018						
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: Q01263-X