



Rowe Industries | 626 Main St. | Ceredo, WV 25507 |
Ph 302-855-0585, Fax 302-855-9182
www.roweindustries.com

STANDARD MANUFACTURING PROCEDURE

SMP#: SW16BQ3THE
CUSTOMER:
ORDER-LINE-RELEASE NUMBER:
COLOR:BLACK

PART DESCRIPTION: #16 26/30 TC UL 3239 20KV & CSA FLEXLEAD SR WIRE

DIMENSIONS: #16 AWG - 26/30 TC NOMINAL OD: 0.057"
STRAND DIAMETER: 0.010"
CONDUCTOR WEIGHT: 8.3 Lbs/M'
FINISHED WIRE OD: 0.150" +/- 0.003 "
MINIMUM AVG. WALL: 0.045"
MINIMUM WALL AT ANY POINT: 0.0405"

RU AWM STYLE 3239 150C 20KVDC VW-1 E61355 CSA LL103756 TV-20 150C FT-1 16 AWG

(*) SPARK VOLTAGE: 15 KVAC

REVISION INFORMATION						
REV.	DESCRIPTION	ECO NUMBER	DATE	BY	DEPT HEAD	ENG
A	Org.	Ecn-9777	7/17/17	JAD	JAD	E ROWE