



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 74-285

CONSTRUCTION SPECIFICATIONS

Description AWM 15C 22 AWG Unshielded
Conductor 22 AWG 7 Strand Tinned Copper - Concentric
Conductor Diameter 0.030"
Insulation Type Semi Rigid PVC
Insulation Thickness 0.008"
Conductor Identification Black, White, Red, Green, Orange, Blue, White/Black, Red/Black, Green/Black, Orange/Black, Blue/Black, Black/White, Red/White, Green/White, Blue/White
Ripcord Polyester Ripcord included under the cable jacket
Jacket Flame Retardant PVC
Jacket Thickness 0.023" (minimum average)
Overall Cable Diameter 0.270"
Jacket Print CSA CMG 60C 22 AWG LL83251 (UL) CM 22 AWG E129985 CSA AWM II A/B105C 600V FT4 LL67097 ROHS (work order)

ELECTRICALS

Voltage 300V; CMG, CM / 600V; AWM II
Conductor Resistance 16.7 Ohms/Mft @20C
Capacitance 27 pF/ft

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified *CSA C22.2 No. 214, Communications Cables
 *CSA C22.2 No. 210.2, Appliance Wiring Material Products
UL Listed *UL 444, Communications Cables
Flame Test Rating CSA FT4
Temperature Rating 60C; CMG, CM / 105C; AWM II
ROHS Compliant
Cable Weight 80 kg/km
Copper Content 47 kg/km
Max Pull Tension 52 kgs
Min Bending Radius 3.25 inches (installed)
Min Installation Temp -20C

Rev. 000

27-Aug-12