

UL Style 3311

Appliance Wiring

90°C - 600 volts AC - Horizontal Flame

Features

Conductors available in solid or stranded, tinned or copper
Insulation: 90°C EPDM
RoHS and REACH Compliant

Compliances

CSA CL-905
Voltage Rating 600 volts AC
Horizontal Flame per UL 1581
UL 758

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors for base and stripe combinations
Packaging options: reels, drums, returnable containers

Applications

Motor leads and internal wiring of appliances

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Nom OD (in)	Min Wall (in)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
8	133	29	0.162	0.353	0.072	102	53
6	266	30	0.200	0.370	0.072	131	82
4	420	30	0.255	0.425	0.072	191	133
2	665	30	0.305	0.485	0.072	277	205
1	836	30	0.355	0.550	0.072	359	258
1/0	1064	30	0.405	0.625	0.086	449	328
2/0	1330	30	0.447	0.650	0.086	523	409
3/0	1672	30	0.515	0.755	0.086	676	516
4/0	2109	30	0.562	0.800	0.086	825	663

Customer Service Group

1 Prestolite Drive


Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.Prestolitewire.com

Email: bulkwiresales@prestolitewire.com



Rev: -0-