



# Specification Sheet

## Lake Cable Part #: RFH16(26)T-06

**Description:** 16 AWG 1 conductor 26 strand tinned copper with XLPE insulation, unshielded 600V cable, approved for use in RFH-2/FFH-2/XLPE, UL AWM 3320 and CSA AWM I A applications.

### 1. Conductor

- 1.1. AWG Size & Stranding: 16 AWG 26 Strands Class K
- 1.2. Material: Annealed Tinned Copper
- 1.3. Conductor Count: 1 Conductor

### 2. Insulation

- 2.1. Material: Cross-linked Polyethylene
- 2.2. Wall Thickness: 0.030"
- 2.3. Color Code: Blue
- 2.4. Diameter: 0.119"
- 2.5. Weight: 15 lbs./Mft.

### 3. Assembly

- 3.1. Lay Length: N/A
- 3.2. Fillers: N/A
- 3.3. Binder: N/A
- 3.4. Shield: N/A
- 3.5. Drain Wire: N/A

### 4. Markings

- 4.1. Type: Conductors shall be permanently identified via surface inkjet print
- 4.2. Legend: LAKE CABLE E207518 (UL) RFH-2/FFH-2/XLPE 16AWG 600V 90°C AWM 3320 CSA AWM I A 90°C 600V FT2 226471 "ROHS II" REACH MADE IN USA
- 4.3. Footage Markers: No

### 5. Standards

- 5.1. Meets all requirements of UL Standard 66 for Type RFH-2/FFH-2
- 5.2. Meets all requirements of UL AWM 3320 600V
- 5.3. Meets all requirements of CSA AWM I A 600V
- 5.4. All materials used in the manufacture of this cable are RoHS II & REACH compliant
- 5.5. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**