

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: 3321-6-133-T
Customer Part Number: 3321/06T133-0-TH

Description: 6 GA AWM UL3321 150 DEGC 600V XLPE
133 STRANDS TINNED COPPER

Conductor (Stranding): 133 x 27 AWG Tinned Copper Lay =2.5", UL
Conductor OD (Nom) 0.190 inches
Max. Lay Length: 2.5 inch Lay
Min Avg Wall Thickness: 0.045 inches
Nom. O. D: 0.284 inches
Min O. D: 0.281 inches
Max Runout: 0.015 inches
Separator: One 1" Paper
Circular Mils (CMA): 25715 (Min)
Surface Print: 6AWG RU AWM STYLE 3321 150C XLPE 600V
E 11352 CSA AWM IA 150C 600V FT2 LL 12201

This Product is RoHS Compliant.

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
UL : AWM 3321/ STD 758	CSA: C22.2 #210-05	Packard: N/A
Other: N/A		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Quality Engineer)

Date: 8-9-2011
Mat'l Spec Form (#F-0270)

Rev. 0

7-30-1998