

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: 3321-12-65-T
Spec Revision Level: A12
Customer Part Number: 3321/12T65-0

Description: 12 GA AWM UL3321 150 DEGC 600V XLPE
65 STRANDS TINNED COPPER

Conductor (Stranding): 65 x 30 AWG Tinned Copper, UL
Conductor OD (Nom) 0.089 inches
Max. Lay Length: 2.0 inch Lay
Min Avg Wall Thickness: 0.030 inches
Nom. O. D: 0.153 inches
Min O. D: 0.150 inches
Max Runout: 0.008 inches
Insulation Strip Limits: 1" Strippable
Circular Mils (CMA): 6334 (Min)
Surface Print: 12 AWG RU AWM STYLE 3321150C XLPE 600V
E11352 CSA AWM IA 150C 600V FT2 LL12201

This product is RoHS Compliant

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
UL : AWM 3321/ STD 758	CSA: C22.2 #210-05	Packard: N/A
Other: N/A		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Product Engineering Manager)
Date: 5-30-2019