

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: **3321-F-22-1001**
Spec Revision Level: A3
Customer Part Number: 3321/22T07-0-TH

Description: 22 GA AWM UL3321 150 DEGC 600V XLPE
VW-1, 7 STRANDS TINNED COPPER

Conductor (Stranding): 7 x 30 AWG Tinned Copper , UL
Conductor OD (Nom) 0.029 inches
Max. Lay Length: 0.75 inch Lay
Min Avg Wall Thickness: 0.030 inches
Nom. O. D: 0.093 inches
Min O. D: 0.090 inches
Max Runout: 0.008 inches
Low End Temp Rating : Minus 10 DegC (Continuous Operation)
Strip Force: 3 lb (min)- 12 lb (max)
Circular Mils (CMA): 573 (Min)
Surface Print: 22 AWG RU AWM STYLE 3321 150C XLPE 600V
VW-1 E11352 CSA AWM IA 150C 600V FT2 LL12201

This product is RoHS Compliant

Specification Reference Data

SAE: N/A	Ford: N/A	Chrysler: N/A
UL : AWM 3321/ STD 758/1581	CSA: C22.2 #210-05	Packard: N/A
Other: N/A		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Product Engineering Manager)

Date: 1-2-2018