



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 74-998

CONSTRUCTION SPECIFICATIONS

Description	AWM 15 Conductor 18 AWG Unshielded
Conductor	18 AWG 16 Strand Tinned Copper - Bunched
Conductor Diameter	0.047"
Insulation Type	Semi Rigid PVC
Insulation Thickness	0.012"
Conductor Identification	Black, White, Red, Green, Orange, Blue, White/Black, Red/Black, Green/Black, Orange/Black, Blue/Black, Black/White, Red/White, Green/White, Blue/White
Ripcord	Polyester Ripcord included under the cable jacket
Jacket	Flame Retardant PVC
Jacket Thickness	0.030" (minimum average)
Overall Cable Diameter	0.410"
Jacket Print	CSA AWM II A/B105C 600V FT4 LL67097 CMG 18 AWG 60C LL83251 RU AWM STYLE 2464 80C 300V E111002 ROHS (work order)

ELECTRICALS

Voltage	300V; CMG, AWM STYLE 2464 / 600V; AWM II
Conductor Resistance	7.15 Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	*CSA C22.2 No. 214, Communications Cables *CSA C22.2 No. 210.2, Appliance Wiring Material Products
UL RECOGNIZED	*UL 758, Appliance Wiring Material
Flame Test Rating	CSA FT4
Temperature Rating	60C; CMG / 105C; AWM II / 80C; AWM STYLE 2464
ROHS	Compliant
Cable Weight	179.89 kg/km
Copper Content	109.88 kg/km
Max Pull Tension	120 kgs
Min Bending Radius	5.00 inches (installed)
Min Installation Temp	-20C

Rev. 000

4-Nov-10