



UL STYLE 3614
4/0 2109X30T 3614 BK

125°C/150°C No Flex, 1000 Vac, Horizontal flame

Conductor

Size: 4/0 ga
 Number of Strands: 2109
 Strand Diameter, Nom: 30 ga (0.0100 in)
 Conductor: Tinned Copper

Insulation

Insulation Material: 125°C/150°C No Flex EPDM
 Min Wall: 1.83 mm (0.072 in)
 Nom Wall: 2.03 mm (0.080 in)
 Diameter, Min: 19.30 mm (0.760 in)
 Diameter, Max: 20.57 mm (0.810 in)
 Strip Force, Min: 4 lbs. (17.8 N)
 Strip Force, Max: 40 lbs. (178.0 N)
 Separator: Physical

Voltage Rating: 1000 Vac
 Temperature Rating: -40°C to 125°C/150°C No Flex
 Print Legend: 4/0 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125°C/150°C 600V/1000V
 PRESTOLITE P.G. CSA CL-1503 OR AWM I A/B 125°C 600V FT2
 Specifications: UL: 3340/3374/3614
 CSA: CL-1503/AWM
 Packaging: Reels
 Color: Black
 Part Number: 145946-81IE
 Other: RoHS Compliant