



Deca Cables Inc.  
 150 North Murray Street  
 P.O. Box 777  
 Trenton, Ontario K8V 5W6  
 Canada

Website: www.decacables.com  
 Telephone: (613) 392-3585  
 Facsimile: (613) 392-7908  
 Email: sales@decacables.com

**ISO 9001:2008**

**PRODUCT DATA SHEET**

**Part No: 74-324**

CONSTRUCTION SPECIFICATIONS

<b>Description</b>	AWM 2C 14 AWG Unshielded
<b>Conductor</b>	14 AWG 41 Strand Tinned Copper
<b>Conductor Diameter</b>	0.074"
<b>Insulation Type</b>	Semi Rigid PVC
<b>Insulation Thickness</b>	0.020"
<b>Cable Assembly</b>	Conductors are together with an overall PVC jacket.
<b>Shield Material</b>	None
<b>Drain Wire</b>	None
<b>Ripcord</b>	Polyester Ripcord included under the cable jacket
<b>Jacket</b>	Flame Retardant PVC
<b>Jacket Thickness</b>	0.030" (minimum average)
<b>Overall Cable Diameter</b>	0.298"
<b>Jacket Print</b>	CSA AWM II A/B105C 600V FT4 LL67097 .... RU AWM STYLE 2464 80C 300V E111002 ROHS (work order)

ELECTRICALS

<b>Voltage</b>	600V; AWM II      300V; AWM STYLE 2464
<b>Conductor Resistance</b>	2.73      Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

<b>CSA Certified</b>	*CSA C22.2 No. 210.2, Appliance Wiring Material Products
<b>UL RECOGNIZED</b>	*UL 758, Appliance Wiring Material
<b>Flame Test Rating</b>	CSA FT4
<b>Temperature Rating</b>	105C; AWM II / 80C; AWM STYLE 2464
<b>ROHS</b>	Compliant
<b>Cable Weight</b>	73.14      kg/km
<b>Copper Content</b>	36.99      kg/km
<b>Max Pull Tension</b>	41      kgs
<b>Min Bending Radius</b>	3.75      inches (installed)
<b>Min Installation Temp</b>	-20C

Rev. 000

24-Jan-12