



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 74-699

CONSTRUCTION SPECIFICATIONS

Description	AWM 4C 14 AWG Unshielded
Conductor	14 AWG 41 Strand Tinned Copper
Conductor Diameter	0.074"
Insulation Type	Semi Rigid PVC
Insulation Thickness	0.020"
Conductor Identification	Black, White, Red, Green
Ripcord	Polyester Ripcord included under the cable jacket
Jacket	Flame Retardant PVC
Jacket Thickness	0.030" (minimum average)
Overall Cable Diameter	0.347"
Jacket Print	CSA AWM II A/B105C 600V FT4 LL67097 RU AWM STYLE 2464 80C 300V E111002 ROHS (work order)

ELECTRICALS

Voltage	600V; AWM II	300V; AWM STYLE 2464
Conductor Resistance	2.73	Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	*CSA C22.2 No. 210.2, Appliance Wiring Material Products	
UL Recognized	*UL 758, Appliance Wiring Materials	
Flame Test Rating	CSA FT4	
Temperature Rating	80C; STYLE 2464 / 105C; AWM II	
ROHS	Compliant	
Cable Weight	126.27	kg/km
Copper Content	73.98	kg/km
Max Pull Tension	82	kgs
Min Bending Radius	4.25	inches (installed)
Min Installation Temp	-20C	

Rev. 000

4-Oct-11