



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

3-Feb-2015

Product Number : **5202251TFT4**

RoHS

**Mini Shielded Cable 1/PR 22/7 AWG STC
P.O. Insulation
PVC FT-4 Jacket**

Conductor : 22 AWG 7 Strand STC Cond.	
Total Cable Weight : 19 kg/km	Final Diameter : 0.138 inches
Insulation : PO	Jacket : PVC
Shield : Foil Shield	
Drain: 22 AWG 7 Strand STC Cond.	
DC Resistance 25°C: 15.3 Ohms / 1000 ft	Mutual Capacitance : 28.9 pF/ft
Impedance : 60 Ohms	Cond to Shield Cap. : 53.6 pF/ft
Velocity of Prop : 69 %	Inductance. : 1.3 mH/km

Print Notes :

Standard Print : ECI ELECTROCOM c CSA us CMG 75°C LL61365 OR CSA AWM II A/B 75°C
600V FT-4 22 AWG RoHS

(All of the above values are approximated to within +/- 10%)

5202251TFT4