



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

8-Oct-2014

Product Number : 5032204TFT4

RoHS

**O/A SH CABLE 4/C 22/7 AWG STC
PO Insulation
Gray PVC FT-4 Jacket**

Conductor : 22 AWG 7x.0097 Tin Copper	
Total Cable Weight : 35 kg/km	Final Diameter : 0.193 inches
Insulation : LDPE	Jacket : PVC
Shield : Foil Shield 0.625	
Drain: 24 AWG 7 Strand STC Cond.	
DC Resistance 25°C: 15.3 Ohms / 1000 ft	Mutual Capacitance : 19.6 pF/ft
Impedance : 75 Ohms	Cond to Shield Cap. : 35.9 pF/ft
Velocity of Prop : 68 %	Inductance. : 1.3 mH/km

Print Notes :

Standard Print : ECI ELECTROCOM CSA-C/US CMG 75°C LL61365 OR CSA AWM II A/B 75°C
600V FT-4 22 AWG RoHS

(All of the above values are approximated to within +/- 10%)

5032204TFT4