

PROVO PART NUMBER  
**2063**

**MULTI-PAIR - INDIVIDUAL FOIL SHIELD • EACH PAIR 100% ALUMINUM FOIL SHIELD • STRANDED TINNED COPPER CONDUCTORS • TWISTED PAIRS • POLYPROPYLENE INSULATION • EACH PAIR STRANDED TINNED COPPER DRAIN WIRE • PVC JACKET • -20°C +80°C**



SPEC CRITERIA	SPECIFICATION
AWG	20
STRANDING	7 x 28
NUMBER OF PAIRS	3
DRAIN WIRE AWG	22
INSULATION TYPE	PP
INSULATION THICKNESS	0.010
JACKET TYPE	PVC
JACKET THICKNESS	0.023
NOM. CABLE OD	0.26
NOMINAL CAPACITANCE *	30
NOMINAL CAPACITANCE **	55
VOLTAGE	600
TEMPERATURE	-20°C to +80°C
PUT-UP METERS	300 / 150
WEIGHT (LBS)	50 / 25
CSA	<b>AWM, CMG, FT-4</b>
UL	<b>CMG, UL444</b>
RoHS	<b>COMPLIANT</b>
FLAME TEST	FT-4
COLOUR CODE	1) Black w/Red 2) Black w/White 3) Black w/Green

\* Capacitance between conductors.

\*\* Capacitance between one conductor and other conductors connected to shield.