

SPECIFICATION CONTROL DRAWING

FLHT+0311


TITLE HIGH TEMPERATURE HOOKUP WIRE, RADIATION-CROSSLINKED, MODIFIED ETFE INSULATED, 600 VOLT

Date 1-24-05

Revision T

The complete requirements for procuring the wire described herein shall consist of this document and the issue in effect of Raychem Specification WCD 3106 and UL Subject 758, Style 3557, File E38136 and carries UL labels to this effect.

CONDUCTOR - TIN-COATED COPPER



INSULATION - RADIATION-CROSSLINKED, MODIFIED ETFE

TABLE I. CONSTRUCTION DETAILS

PART NUMBER 1/	WIRE SIZE (AWG)	CONDUCTOR STRANDING (number x AWG)	TARGET CONDUCTOR DIAMETER (in.) (mm)	FINISHED WIRE					NOMINAL WEIGHT (lbs/1000 ft.) (kg/km)
				MAXIMUM RESISTANCE AT 20°C (ohms/1000 ft.) (ohms/km)	DIAMETER (in.) (mm)				
					MINIMUM	NOMINAL	MAXIMUM		
FLHTB0311-28-**	28	7 x 36	.0145 (.368)	72.8 (239.)	.0271 (.688)	.0285 (.724)	.0299 (.759)	.86 (1.28)	
FLHTB0311-18-**	18	7 x 26	.0465 (1.18)	7.06 (23.2)	.0584 (1.48)	.0601 (1.53)	.0618 (1.57)	5.95 (8.85)	
FLHTB0311-16-**	16	7 x 24	.0600 (1.52)	4.45 (14.6)	.0731 (1.86)	.0750 (1.91)	.0769 (1.95)	9.75 (14.5)	
FLHTB0311-14-**	14	7 x .0242" 2/	.0726 (1.84)	2.90 (9.51)	.0865 (2.20)	.0886 (2.25)	.0907 (2.30)	14.6 (21.7)	
FLHTC0311-26-**	26	19 x 38	.0185 (.470)	45.8 (150.)	.0301 (.765)	.0315 (.800)	.0329 (.836)	1.27 (1.89)	
FLHTC0311-24-**	24	19 x 36	.0235 (.597)	28.7 (94.2)	.0351 (.892)	.0365 (.927)	.0379 (.963)	1.85 (2.75)	
FLHTC0311-22-**	22	19 x 34	.0295 (.749)	18.1 (59.4)	.0411 (1.04)	.0425 (1.08)	.0439 (1.12)	2.74 (4.08)	
FLHTC0311-20-**	20	19 x 32	.0375 (.953)	11.4 (37.4)	.0491 (1.25)	.0505 (1.28)	.0519 (1.32)	4.17 (6.21)	
FLHTC0311-18-**	18	19 x 30	.0465 (1.18)	7.15 (23.5)	.0583 (1.48)	.0600 (1.52)	.0617 (1.57)	6.34 (9.43)	
FLHTC0311-16-**	16	19 x 29	.0525 (1.33)	4.82 (15.8)	.0656 (1.67)	.0675 (1.71)	.0694 (1.76)	8.09 (12.0)	
FLHTC0311-14-**	14	19 x 27	.0660 (1.68)	3.05 (10.0)	.0799 (2.03)	.0820 (2.08)	.0841 (2.14)	12.5 (18.6)	
FLHTC0311-12-**	12	19 x 25	.0900 (2.29)	1.92 (6.30)	.1035 (2.63)	.1060 (2.69)	.1085 (2.76)	22.4 (33.3)	
FLHTD0311-12-**	12	37 x 28	.0850 (2.16)	2.01 (6.59)	.0984 (2.50)	.1010 (2.57)	.1036 (2.63)	19.3 (28.7)	
FLHTD0311-10-**	10	37 x 26	.107 (2.72)	1.26 (4.13)	.121 (3.07)	.125 (3.18)	.129 (3.28)	30.7 (45.7)	
FLHTE0311- 8-**	8	133 x 29	.160 (4.06)	.701 (2.30)	.175 (4.45)	.180 (4.57)	.185 (4.70)	54.9 (81.7)	

2/ Nominal Strand Diameter

Due to UL limitations on the usage of small strand bare and tin plated conductors, products with conductor strand diameters less than .015" (.381 mm) are intended for dry locations only. For wet locations, other UL Recognized products are available.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL.

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.



Raychem Wire & Cable
501 Oakside Avenue
Redwood City, CA 94063-3800
Phone: 1-800-227-8816
Fax: 1-650-361-6297

TABLE II. PERFORMANCE DETAILS			
PART NUMBER 1/	BEND TESTING		
	MANDREL DIAMETER (inch) (mm) (± 3%)		WEIGHT (lb) (kg) (± 3%)
	CROSSLINK VERIFICATION		CROSSLINK VERIFICATION
FLHTB0311-28-*	.375	(9.53)	.125 (.057)
FLHTB0311-18-*	.500	(12.7)	1.00 (.454)
FLHTB0311-16-*	.750	(19.1)	1.50 (.680)
FLHTB0311-14-*	1.00	(25.4)	2.00 (.907)
FLHTC0311-26-*	.375	(9.53)	.125 (.057)
FLHTC0311-24-*	.375	(9.53)	.500 (.227)
FLHTC0311-22-*	.500	(12.7)	.750 (.340)
FLHTC0311-20-*	.500	(12.7)	1.00 (.454)
FLHTC0311-18-*	.500	(12.7)	1.00 (.454)
FLHTC0311-16-*	.750	(19.1)	1.50 (.680)
FLHTC0311-14-*	1.00	(25.4)	2.00 (.907)
FLHTC0311-12-*	1.50	(38.1)	3.00 (1.36)
FLHTD0311-12-*	1.50	(38.1)	3.00 (1.36)
FLHTD0311-10-*	2.00	(50.8)	3.00 (1.36)
FLHTE0311- 8-*	3.00	(76.2)	4.00 (1.81)

WIRE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C
 VOLTAGE RATING: 600 volts (rms) at sea level
 CROSSLINK VERIFICATION: 300 ± 3°C for 1 hour
 FLAME RATING: VW-1

INSULATION ELONGATION AND TENSILE STRENGTH:
 Elongation, 100% (minimum)
 Tensile Strength, 5470 lbf/in² (minimum)

INSULATION FLAWS:
 Spark Test, 6.0 kV (rms)
 Impulse Dielectric Test, 8.0 kV (peak)

INSULATION THICKNESS:
 AWG 28 - 16: 0.0055 inch (minimum)
 0.006 inch (minimum average)
 AWG 14: 0.006 inch (minimum)
 0.0065 inch (minimum average)
 AWG 12: 0.0065 inch (minimum)
 0.007 inch (minimum average)
 AWG 10: 0.007 inch (minimum)
 0.0075 inch (minimum average)
 AWG 8: 0.0075 inch (minimum)
 0.008 inch (minimum average)

SHRINKAGE: 0.125 in. (maximum) per end at
 200°C for 1 hour
 THERMAL STABILITY: 232°C
 Elongation, 60% (minimum)
 Tensile Strength, 5000 lbf/in² (minimum)
 VOLTAGE WITHSTAND TEST (Post Environmental):
 2500 volts (rms), 60 Hz, 5 minutes

PART NUMBER:
 The "+" in the part number in the upper right hand corner
 of page 1 and 2 shall be replaced with a letter designator to define
 conductor stranding (see part numbers in table).
 B = 7 Strands C = 19 Strands D = 37 Strands E = Rope Lay

The "*" in the part numbers in the table shall be replaced by
 color code designators.
 1/ Example: AWG 22, 19 strand, white: FLHTC0311-22-9
 AWG 22, 19 strand, white with black stripe:
 FLHTC0311-22-90

SPOOL LABEL: All spool/reel labels containing conductor strand diameters less than .015" (.381 mm) shall include: "For Dry Locations Only".

1/ See footer on page 1