



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

18-Apr-2013

Product Number : **5152454TFT4**

RoHS

**O/A SH CABLE 4/PR 24/7 AWG STC
SR-PVC Insulation
Gray PVC FT4 Jacket**

Conductor : 24 AWG 7 Strand STC Cond.

Total Cable Weight : 42 kg/km	Final Diameter : 0.224 inches
-------------------------------	-------------------------------

Insulation : SR-PVC	Jacket : PVC
---------------------	--------------

DC Resistance : 26.5 @ 25°C Ohms	Mutual Capacitance : 23.1 pF/ft
----------------------------------	---------------------------------

Impedance : 80 Ohms	Cond to Shield Cap. : 36.6 pF/ft
---------------------	----------------------------------

Velocity of Prop : 64 %	Inductance. : 1.3 mH/km
-------------------------	-------------------------

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105'C LL61365 OR CSA AWM II A/B 105'C 600V
FT-4 (UL) CMG E132883 105'C #24 AWG RoHS

(All of the above values are approximated to within 10%)